



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: ACRYLIC ENAMEL REDUCER SLOW
PRODUCT CODE: 153

Page 1 of 6
DATE: 7/12/2007

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this MSDS before handling and disposing of this product.

Pass this information on to employees, customers, & users of this product.

SECTION 1. CHEMICAL PRODUCTS & COMPANY IDENTIFICATION / HAZARD RATINGS

PRODUCT NAME: Blend# 9907 Acrylic Enamel Reducer Slow HEALTH RATINGS:
HEALTH (NFPA) = 2
GENERAL OR GENERIC ID: SOLVENT BLEND HEALTH (HMIS) = 3
COMPANY NAME: PBE Jobbers Warehouse FLAMMABILITY = 3
COMPANY ADDRESS: 2899 Syene Road REACTIVITY = 0
Madison, WI 53713
COMPANY PHONE: 1-800-225-5723
EMERGENCY PHONE: 1-800-424-9300

SECTION 2. INGREDIENT & REGULATORY INFORMATION

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

Table with 5 columns: SARA TITLE III INGREDIENTS, CAS#, WT. %, (REG.SECTION), RQ (LBS). Rows include Toluene, Light Aliphatic Solvent Naphtha, Acetone, *2-Butoxyethanol, *Mixed Xylenes, *Methanol, and *Ethylbenzene.

SARA SECTION 311/312 HAZARDS: Acute Health, Chronic Health, Fire

Table with 5 columns: MATERIAL, CAS#, TWA (OSHA), TLV (ACGIH), HAP. Rows include Toluene, Light Aliphatic Solvent Naphtha, Acetone, and Ethylbenzene.



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: ACRYLIC ENAMEL REDUCER SLOW
PRODUCT CODE: 153

2-Butoxyethanol				
Mixed Xylenes	1330-20-7	100 ppm	100 ppm	Yes
Methanol	67-56-1	200 ppm (s)	200 ppm (s)	Yes
Ethylbenzene	100-41-4	100 ppm	100 ppm	Yes

In addition to EPA Hazardous Air pollutants showing 'Yes' under "HAP" above, using manufacturers' data, based on EPA Method 311, the following EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%) = Benzene, Cumene

MATERIAL	CAS#	CEILING	STEL (OSHA/ACGIH)
Light Aliphatic Solvent Naphtha	*64742-89-8	None Known	0 ppm
Acetone	67-64-1	None Known	1000 ppm
Mixed Xylenes	1330-20-7	None Known	150 ppm
Methanol	67-56-1	None Known	250 ppm
Ethylbenzene	100-41-4	None Known	125 ppm

CALIFORNIA PROPOSITION 65: This product contains the following chemicals known to the state of California to cause cancer & reproductive toxicity: Ethylene Glycol Butyl Ether, a trace of Benzene, Toluene
IF > 2366 POUNDS OF THIS PRODUCT IS IN ONE CONTAINER THE "RQ" IS EXCEEDED.

DOT SHIPPING NAME: Paint Related Material, 3, UN1263, PG II

DRUM LABEL: (FLAMMABLE LIQUID)

SECTION 3. HAZARDS IDENTIFICATION

MATERIAL	CAS#	LOWEST KNOWN LETHAL DOSE DATA
Ethylene Glycol Butyl Ether	111-76-2	LOWEST KNOWN LD50 (ORAL) 320.0 mg/kg (Rabbits)
Ethylene Glycol Butyl Ether	111-76-2	LOWEST KNOWN LC50 (VAPORS) 700 ppm (Mice)
Ethylene Glycol Butyl Ether	111-76-2	LOWEST KNOWN LD50 (SKIN) 440.0 mg/kg (Rabbits)

THRESHOLD LIMIT VALUE: 75 ppm (Evaporated Blend)

CONTAINS: TOLUENE, LIGHT ALIPHATIC SOLVENT NAPHTHA, ACETONE, 2-BUTOXYETHANOL, MIXED XYLENES, METHANOL, ETHYLBENZENE

DANGER!!
EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE
ACUTE HAZARDS

EYE & SKIN CONTACT:

- Primary irritation to skin, defatting, dermatitis.
- Absorption through skin increases exposure.
- Primary irritation to eyes, redness, tearing, blurred vision.



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: ACRYLIC ENAMEL REDUCER SLOW

PRODUCT CODE: 153

Page 3 of 6

Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.

Breathing vapor can cause irritation.

Acute overexposure can cause damage to kidneys, blood, nerves, liver & lungs.

SWALLOWING:

Harmful or fatal if swallowed.

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

SUBCHRONIC HAZARDS / CONDITIONS AGGRAVATED

CONDITIONS AGGRAVATED

Chronic overexposure can cause damage to kidneys, blood, nerves, liver, & lungs.

Persons with severe skin, liver or kidney problems should avoid use.

CHRONIC HAZARDS

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

Potential Cancer Hazard based on tests with laboratory animals using Ethylene Glycol Butyl Ether & a trace of Benzene.

Liver tumors have been reported in laboratory mice.

Overexposure may create cancer risk.

This product may contain less than 147 ppm of Benzene.

Not considered hazardous in such low concentrations.

Absorption thru skin may be harmful. Studies with laboratory animals indicate this product can cause damage to fetus.

SECTION 4. FIRST AID MEASURES PROCEDURES

EYE CONTACT:

For eyes, flush with plenty of water for 15 minutes & get medical attention.

SKIN CONTACT:

In case of contact with skin immediately remove contaminated clothing.

Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

(Discard contaminated shoes)

INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped give artificial respiration. **CALL A PHYSICIAN IMMEDIATELY!**

SWALLOWING:

If swallowed, **CALL A PHYSICIAN IMMEDIATELY!** Do NOT induce vomiting.

Have patient lie down & keep warm. Vomiting may lead to pneumonitis, which may be fatal



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: ACRYLIC ENAMEL REDUCER SLOW
PRODUCT CODE: 153

Page 4 of 6

SECTION 5. FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE: 287 C / 550 F (Lowest Component)
LOWER FLAMMABLE LIMIT IN AIR (% by vol): 1.6
FLASH POINT (TEST METHOD): -16 C / 2 F (TCC)
FLAMMABILITY CLASSIFICATION: Class I B
EXTINGUISHING MEDIA

NFPA Class B extinguishers (Carbon Dioxide or foam) for Class I B liquid fires.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire fighters & cool closed containers. Use fog nozzles if water is used.

Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots).

Use NIOSH approved positive-pressure self-contained breathing apparatus.

UNUSUAL EXPLOSION AND FIRE PROCEDURES

EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE

Keep container tightly closed.

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

Closed containers may explode if exposed to extreme heat.

Applying to hot surfaces requires special precautions.

Empty container very hazardous! Continue all label precautions

SECTION 6. ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES

Stop spill at source. Dike area & contain. Clean up remainder with absorbent materials. Mop up & dispose of. Persons without proper protection should be kept from area until cleaned up.

WASTE DISPOSAL METHOD

Recycle or dispose of observing local, state & Federal health, safety & pollution laws. If questions exist, contact the appropriate agencies.

OTHER PRECAUTIONS

Vapors may ignite explosively & spread long distances. Prevent vapor buildup. Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone.

SECTION 7. HANDLING AND STORAGE

HANDLING

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

Use only with adequate ventilation. Avoid breathing of vapor or spray mist.

Do not get in eyes, on skin or clothing.

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier.

Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: ACRYLIC ENAMEL REDUCER SLOW
PRODUCT CODE: 153

Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

STORAGE

Vapors may ignite explosively & spread long distances. Prevent vapor buildup.

Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone.

Do not store above 49 C / 120 F. Store large amounts in structures made for OSHA Class I B liquids.

Keep container tightly closed & upright when not in use to prevent leakage.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Ventilate to keep vapors of this material below 40 ppm. If over TLV, in accordance with 29 CFR 1910.134, use NIOSH approved positive-pressure self-contained breathing apparatus. Consult Safety Equipment Supplier. Use explosion-proof equipment.

VENTILATION

- LOCAL EXHAUST = Necessary
- MECHANICAL (GENERAL) = Acceptable
- SPECIAL = None
- OTHER = None

PERSONAL PROTECTIONS:

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier.

Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

SECTION 9. PHYSICAL DATA

- APPEARANCE: Liquid, Water-White
- ODOR: Ketone
- BOILING RANGE: 57 91 172 C / 135 197 342 F
- GRAVITY @ 60 F:
- API: 40.3
- SPECIFIC GRAVITY (Water = 1): .824
- POUNDS / GALLON: 6.862
- VOC'S (>0.44 LBS / SQ IN): 89.2 Vol. % / 734.4 g/L / 6.117 Lbs/Gal
- TOTAL VOC'S (TVOC): 100.0 Vol. % / 823.7 g/L / 6.861 Lbs/Gal
- NONEXEMPT VOC'S (CVOC): 85.5 Vol. % / 708.9 g/L / 5.904 Lbs/Gal
- HAZARDOUS AIR POLLUTANTS (HAPS): 56.6 Vol. % / 466.3 g/L / 3.884 Lbs/Gal
- VAPOR PRESSURE (mm of Hg) @ 20 C: 58.7
- NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C): 19.4
- VAPOR DENSITY (air = 1): 3.0
- WATER ABSORPTION: Appreciable
- SOLVENCY PARAMETERS:



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: ACRYLIC ENAMEL REDUCER SLOW
PRODUCT CODE: 153

Page 6 of 6

HKB (Hydrogen Bonding):	21.5
PKB (Polarity):	38.4
DKB (Dispersion):	40.1
REFRACTIVE INDEX:	1.440
MIXED ANILINE POINT (Acid Insol):	31 C / 88 F

SECTION 10. REACTIVITY DATA

STABILITY

Stable

CONDITIONS TO AVOID

Isolate from oxidizers, heat, sparks, electric equipment, & open flame.

MATERIALS TO AVOID

Isolate from strong oxidizers such as permanganates, chromates, & peroxides.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide from burning.

HAZARDOUS POLYMERIZATION

Will not occur.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and / or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.