



M A T E R I A L   S A F E T Y   D A T A   S H E E T

**PRODUCT NAME: URETHANE REDUCER SLOW**  
**PRODUCT CODE: 163**

Page 1 of 6  
DATE: 7/12/2007

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)  
IMPORTANT: Read this MSDS before handling and disposing of this product.  
Pass this information on to employees, customers, & users of this product.

**SECTION 1. CHEMICAL PRODUCTS & COMPANY IDENTIFICATION / HAZARD RATINGS**

PRODUCT NAME:	Blend# 2010 Urethane Reducer Slow	HEALTH RATINGS:	
		HEALTH (NFPA) =	1
GENERAL OR GENERIC ID:	SOLVENT BLEND	HEALTH (HMIS) =	2
COMPANY NAME:	PBE Jobbers Warehouse	FLAMMABILITY =	3
COMPANY ADDRESS:	2899 Syene Road Madison, WI 53713	REACTIVITY =	0
COMPANY PHONE:	1-800-225-5723		
EMERGENCY PHONE:	1-800-424-9300		

**SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS**

CONTAINS: 25-30% PROPYLENE GLYCOL METHYL ETHER ACETATE (108-65-6)  
10-20% METHYL ETHYL KETONE (78-93-3)[201-159-0]  
5-15% LIGHT ALIPHATIC SOLVENT NAPHTHA (\*64742-89-8)  
5-15% ETHYL-3-ETHOXY PROPIONATE (763-69-9)  
5-15% N-BUTYL ACETATE (123-86-4)[204-658-1]  
5-15% TOLUENE (108-88-3) [203-625-9]  
0-5% MIXED XYLENES (1330-20-7) [215-535-7]

**SECTION 3. HAZARDS IDENTIFICATION**

**RISK STATEMENTS:**

R11 Highly Flammable.  
R18 In use, may form flammable/explosive vapor-air mixture.  
R65 Harmful: may cause lung damage if swallowed.  
R36/37/38 Irritating to eyes, respiratory system and skin.  
R20/65 Harmful by inhalation, may cause lung damage if swallowed.

**SAFETY STATEMENTS:**

S9 Keep container in a well-ventilated place.  
S16 Keep away from sources of ignition. No smoking.  
S29 Do not empty into drains.  
S45 In case of accident, or if you feel unwell, seek medical advice immediately. (Show the label where possible).  
S53 Avoid exposure – Obtain special instructions before use.  
S24/25 Avoid contact with skin and eyes.

**SECTION 4. FIRST AID MEASURES**

**EYE CONTACT:**

For eyes, flush with plenty of water for 15 minutes & get medical attention.



## M A T E R I A L   S A F E T Y   D A T A   S H E E T

**PRODUCT NAME: URETHANE REDUCER SLOW**

**PRODUCT CODE: 163**

Page 2 of 6

**SKIN CONTACT:**

In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

**INHALATION:**

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped give artificial respiration.

**SWALLOWING:**

If swallowed, CALL A PHYSICIAN IMMEDIATELY! Do NOT induce vomiting. Have patient lie down & keep warm. Vomiting may lead to pneumonitis, which may be fatal.

### **SECTION 5. FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:**

NFPA Class B extinguishers [Carbon Dioxide or Foam] for Class I B liquid fires.

**SPECIAL FIRE FIGHTING PROCEDURES:**

Water spray may be ineffective on fire but can protect fire fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

**UNUSUAL EXPLOSION AND FIRE PROCEDURES:**

**HIGHLY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE**

Keep container tightly closed.

Isolate from oxidizers, heat, sparks, electric equipment and open flame.

Closed containers may explode if exposed to extreme heat.

Applying to hot surfaces requires special precautions.

Empty container very hazardous! Continue all label precautions!

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

**CONTAINMENT TECHNIQUES:**

Stop spill at source. Dike area & contain.

**CLEAN-UP PROCEDURES:**

Clean up remainder with absorbent materials. Mop up & dispose of. Persons without proper protection should be kept from area until cleaned up.

### **SECTION 7. HANDLING AND STORAGE**

**HANDLING:**

Isolate from oxidizers, heat, sparks, electric equipment & open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin & eyes. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse. Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

**STORAGE:**

Do not store above 49 C / 120 F. Store large amounts in structures made for OSHA Class I B liquids. Keep container tightly closed & upright when not in use to prevent leakage.



M A T E R I A L   S A F E T Y   D A T A   S H E E T

**PRODUCT NAME: URETHANE REDUCER SLOW**  
**PRODUCT CODE: 163**

OSHA Class I B liquids.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**EXPOSURE CONTROLS:**

Use vapor, mist gas mask within use limits, or ventilate to keep vapors of this material below 50 ppm. If over TLV, in accordance with 29 CFR 1910.134, use NIOSH approved positive-pressure self-contained breathing apparatus. Consult Safety Equipment Supplier. Use explosion-proof equipment.

**VENTILATION:**

LOCAL EXHAUST:	Necessary
MECHANICAL (GENERAL):	Acceptable
SPECIAL:	None
OTHER:	None

**PERSONAL PROTECTIONS:**

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

**WORK & HYGIENIC PRACTICES:**

Provide readily accessible eye wash stations & safety showers. Wash at end of each workshift & before eating, smoking or using the toilet. Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

**SECTION 9. PHYSICAL DATA**

APPEARANCE:	Liquid, Water-White
ODOR:	Ketone
BOILING RANGE:	86 120 165* C / 188 249 329* F (*=End Point)
AUTO IGNITION TEMPERATURE:	287 C / 550 F (Lowest Component)
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	1.5
FLASH POINT (TEST METHOD):	-2 C / 28 F (TCC) (Lowest component)
FLAMMABILITY CLASSIFICATION:	Class I B
GRAVITY @ 60 F:	
API:	29.8
SPECIFIC GRAVITY (Water=1):	.877
POUNDS/GALLON:	7.309
VOC'S (>0.44 Lbs./sq. Inch):	51.5 Vol. % / 451.9 g/L / 3.764 Lbs/Gal
TOTAL VOC'S (TVOC):	93.0 Vol. % / 816.0 g/L / 6.797 Lbs/Gal
NONEXEMPT VOC'S (CVOC):	93.0 Vol. % / 816.0 g/L / 6.797 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):	29.1 Wt. % / 244.6 g/L / 2.037 Lbs/Gal
VAPOR PRESSURE (mm of Hg) @ 20 C:	25.9
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C):	25.9
VAPOR DENSITY (air=1):	3.7
WATER ABSORPTION:	Appreciable
REFRACTIVE INDEX:	1.415

**SECTION 10. STABILITY & REACTIVITY**

**STABILITY:**  
Stable



M A T E R I A L   S A F E T Y   D A T A   S H E E T

PRODUCT NAME: URETHANE REDUCER SLOW
PRODUCT CODE: 163

CONDITIONS TO AVOID:
Isolate from oxidizers, heat, sparks, electric equipment & open flame.

MATERIALS TO AVOID:
Isolate from strong oxidizers such as permanganates, chromates & peroxides.

HAZARDOUS DECOMPOSITION PRODUCTS:
Carbon Monoxide, Carbon Dioxide from burning.

HAZARDOUS POLYMERIZATION:
Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

Table with 6 columns: MATERIAL, CAS #, TWA (OSHA), TLV (ACGIH), HAP, and other notes. Rows include Propylene Glycol Methyl Ether Acetate, Methyl Ethyl Ketone, Solvent Naphtha, Ethyl-3-Ethoxypropionate, n-Butyl Acetate, and Mixed Xylenes.

In addition to EPA Hazardous Air Pollutants showing 'Yes' under "HAP" above, using manufacturers' data, based on EPA Method 311, the following EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%): Benzene, Cumene

Table with 4 columns: MATERIAL, CAS #, CEILING, and STEL (OSHA/ACGIH). Rows include Methyl Ethyl Ketone, Light Aliphatic Solvent Naphtha, n-Butyl Acetate, and Mixed Xylenes.

ACUTE HAZARDS

EYE & SKIN CONTACT:
Primary irritation to skin - defatting, dermatitis.
Absorption thru skin increases exposure.
Primary irritation to eyes - redness, tearing, blurred vision.
Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:
Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.
Breathing vapor can cause irritation. Acute overexposure can cause damage to kidneys, blood, nerves, liver & lungs.

SWALLOWING:
Harmful or fatal if swallowed.
Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.



M A T E R I A L   S A F E T Y   D A T A   S H E E T

**PRODUCT NAME: URETHANE REDUCER SLOW**  
**PRODUCT CODE: 163**

Page 5 of 6

**SUBCHRONIC HAZARDS / CONDITIONS AGGRAVATED:**

**CONDITIONS AGGRAVATED:**

Persons with severe skin, liver or kidney problems should avoid use.

**CHRONIC HAZARDS**

**CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:**

Leukemia been reported in humans from Benzene. This product may contain less than 46 ppm of Benzene. Not considered hazardous in such low concentrations. Absorption thru skin may be harmful. Studies with laboratory animals indicate this product can cause damage to fetus.

**SECTION 12. ECOLOGICAL INFORMATION**

**MAMMALIAN INFORMATION:**

MATERIAL	CAS#	LOWEST KNOWN LETHAL DOSE DATA
Toluene	108-88-3	LOWEST KNOWN LD50 (ORAL) 3000.0 mg/kg (Rats)
Methyl Ethyl Ketone	78-93-3	2000 ppm (Rats) LOWEST KNOWN LC50 (VAPORS)
Toluene	108-88-3	LOWEST KNOWN LD50 (SKIN) 4000.0 mg/kg (Rabbits)

**AQUATIC ANIMAL INFORMATION:**

The most sensitive known marine group to any component of this product is:

Flatworm .032 ppm or mg/L (96 hour exposure). Keep out of sewers and natural water supplies.

**MOBILITY:**

This material is a mobile liquid.

**DEGRADABILITY:**

This product is partially biodegradable.

**ACCUMULATION:**

This product does not accumulate or biomagnify in the environment.

**SECTION 13. DISPOSAL CONSIDERATIONS**

Recycle / dispose of observing national, regional, state, provincial and local health, safety & pollution laws. If questions exist, contact the appropriate agencies.

**SECTION 14. TRANSPORT INFORMATION**

DOT SHIPPING NAME: RQ, Paint Related Material

( Contains: Methyl Ethyl Ketone, Toluene) 3, UN1263, PG-II

DRUM LABEL: (FLAMMABLE LIQUID)

IATA / ICAO: RQ, Paint Related Material

( Contains: Methyl Ethyl Ketone, Toluene) 3, UN1263, PG-II

IMO / IMDG: RQ, Paint Related Material

( Contains: Methyl Ethyl Ketone, Toluene) 3, UN1263, PG-II

EMERGENCY RESPONSE GUIDEBOOK NUMBER: 127



M A T E R I A L   S A F E T Y   D A T A   S H E E T

**PRODUCT NAME: URETHANE REDUCER SLOW**  
**PRODUCT CODE: 163**

**SECTION 15. REGULATORY INFORMATION**

**STATE REGULATIONS:**

CALIFORNIA PROPOSITION 65: This product contains the following chemical known to the State of California to cause reproductive toxicity: Toluene

**EPA REGULATIONS:**

SARA SECTION 311/312 HAZARDS: Acute Health, Fire

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <\*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

**SARA TITLE III INGREDIENTS**

	CAS#	WT.%	(REG. SECTION)	RQ (LBS)
*Methyl Ethyl Ketone	78-93-3	16	(311, 312, 313, RCRA) 5000	
*Toluene	108-88-3	10	(311, 312, 313, RCRA)	1000
*Mixed Xylenes	1330-20-7	<2	(311, 312, 313, RCRA)	None

IF > 9168 POUNDS OF THIS PRODUCT IS IN ONE CONTAINER THE "RQ" OF TOLUENE IS EXCEEDED.

**INTERNATIONAL REGULATIONS:**

The components of this product are listed on the chemical inventories of the following countries:

Australia, Canada, Europe (EINECS), Japan, Korea, United Kingdom.

**SECTION 16. OTHER INFORMATION**

**HAZARD RATINGS:**

HEALTH (NFPA):	1
HEALTH (HMIS):	2
FLAMMABILITY:	3
REACTIVITY:	0

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

**EMPLOYEE TRAINING:**

Employees should be made aware of all hazards of this material (as stated in this MSDS) before handling it.

**NOTICE**

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.