



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: Multi-Purpose Clear
PRODUCT CODE: 800

HMIS CODES
Health: 2
Flammability: 3
Reactivity: 0
PPE: G

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER'S NAME:
PBE Jobbers Warehouse

ADDRESS:
2899 Syene Road
Madison, WI 53713

INFORMATION PHONE : (800)-225-5723
EMERGENCY PHONE : (800)-424-9300

DATE PRINTED: 7/12/2007

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

Table with 5 columns: % by WT, CAS No., INGREDIENT, UNITS, and VAPOR PRESSURE. It lists ingredients like Isobutanol, Glycol Ether EB Acetate, Tert Butyl Acetate, Toluene, Xylene, Mixed Isomers, and Ethylbenzene with their respective safety and exposure data.



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: Multi-Purpose Clear
PRODUCT CODE: 800

Page 2 of 7

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE:

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

EFFECTS OF OVEREXPOSURE:

Irritation of eyes, skin and upper respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE:

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

None generally recognized.

CANCER INFORMATION:

FOR COMPLETE DISCUSSION OF TOXICOLOGY DATA REFER TO SECTION 11.

Section 4 -- FIRST AID MEASURES

If INHALED:

If affected, remove from exposure. Restore breathing. Keep warm and quiet.

If on SKIN:

Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

If in EYES:

Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED:

Do not induce vomiting. Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

| FLASH POINT | LEL | UEL |
|-------------|-----|------|
| 0 - 399 F | 0.1 | 10.6 |

EXTINGUISHING MEDIA:

Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical, or universal aqueous film forming foam) designed to extinguish NFPA Class IB flammable liquid fires. Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: Multi-Purpose Clear

PRODUCT CODE: 800

Page 3 of 7

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES:

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbent should be placed in this container.

Section 7 -- HANDLING RELEASE MEASURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and other sources of ignition. Consult NFPA Code. Use approved bonding and grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

Section 8 -- EXPOSURE CONTROLS / PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE:

Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using. This coating may contain materials classified as nuisance particulates (listed "as Dust" section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in section 2, the applicable limits for nuisance dust are ACGIII TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction). Removal of old paint by sanding, scraping, or other means may generate dust or fumes that contain lead.

VENTILATION:

Local exhaust preferable. General exhaust acceptable if the exposure to materials in section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION:

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in section 2. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: Multi-Purpose Clear
PRODUCT CODE: 800

PROTECTIVE GLOVES:

None required for normal application of aerosol products where minimal skin contact is expected. For long repeated contact, wear chemical resistant gloves.

EYE PROTECTION:

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS:

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful of fatal.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

Table with 3 columns: Property, Value 1, Value 2. Rows include PRODUCT WEIGHT, SPECIFIC GRAVITY, BOILING POINT, VOLATILES, EVAPORATION RATE, VAPOR DENSITY, COATING V.O.C., and MATERIAL V.O.C.

Section 10 -- STABILITY AND REACTIVITY

STABILITY:

This product is normally stable and will not undergo hazardous reactions.

CONDITIONS TO AVOID:

None Known.

INCOMPATIBILITY:

Avoid contact with strong alkalis, strong mineral acids, or strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide, carbon dioxide, oxides of sulfur, oxides of barium, lower molecular weight polymer fractions

HAZARDOUS POLYMERIZATION:

None Known.

Section 11 -- TOXICOLOGICAL INFORMATION

CAS No. Ingredient Name

78-83-1 Isobutanol

LC50 RAT 4HR 1430 ppm
LD50 RAT N/E



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: Multi-Purpose Clear
PRODUCT CODE: 800

Page 5 of 7

| | | | | | |
|-----------|-------------------------|------|-----|-----|------------|
| 112-07-2 | Glycol Ether EB Acetate | LC50 | RAT | 4HR | N/E |
| | | LD50 | RAT | | N/E |
| 540-88-5 | Tert Butyl Acetate | LC50 | RAT | 4HR | N/E |
| | | LD50 | RAT | | N/E |
| 108-88-3 | Toluene | LC50 | RAT | 4HR | N/E |
| | | LD50 | RAT | | N/E |
| 1330-20-7 | Xylene, Mixed Isomers | LC50 | RAT | 4HR | 5000 ppm |
| | | LD50 | RAT | | 4300 mg/kg |
| 100-41-4 | Ethylbenzene | LC50 | RAT | 4HR | N/E |
| | | LD50 | RAT | | 3500 mg/kg |

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION:

ECOTOXICITY: No Information Available

ENVIRONMENTAL FATE:

MOBILITY: No Information Available

BIODEGRADATION: No Information Available

BIOACCUMULATION: No Information Available

PHYSICAL/CHEMICAL:

HYDROLYSIS: No Information Available

PHOTOLYSIS: No Information Available

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section 14 -- TRANSPORT INFORMATION

Proper Shipping Name: Consumer Commodity
NOS Technical Name: ORM-D
Hazard Class: N/A
UN Number: N/A
Packing Group: N/A



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: Multi-Purpose Clear
PRODUCT CODE: 800

Page 6 of 7

Section 15 -- REGULATORY INFORMATION

SARA 313:

| CAS No. | CHEMICAL/COMPOUND | % by WT |
|-----------|-------------------------|---------|
| 112-07-2 | Glycol Ether EB Acetate | 0.9 |
| 108-88-3 | Toluene | 0.2 |
| 1330-20-7 | Xylene, Mixed Isomers | 33.5 |
| 100-41-4 | Ethylbenzene | 8.1 |

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects other reproductive harm.

TSCA CERTIFICATION:

U.S. TSCA: This product and/or all of its components are listed on the U.S. TSCA Inventory or is otherwise exempt form TSCA Inventory reporting requirements.

Section 16 -- OTHER INFORMATION

DISCLAIMER:

Do not handle until the manufacturer's safety precautions have been read and understood. Regulations require that all employees be trained on Material Safety Data Sheets for all products with which they come in contact. While we believe that the data contained herein is accurate and derived from qualified sources, the data are not be taken as a warranty or representation for which we assume legal responsibility. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.



M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: Multi-Purpose Clear
PRODUCT CODE: 800

ENVIRONMENTAL DATA SHEET

All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

PRODUCT WEIGHT: 8.358 lb/gal
SPECIFIC GRAVITY: 1.000
FLASH POINT: 0 - 399 F

Table with 7 columns: VOLATILE INGREDIENTS NAME, CAS No., CERC., SARA 313 TC, HAPS 112, PCT by Wt, PCT by Vol. Rows include Glycol Ether EB Acetate, Tert Butyl Acetate, Toluene, Xylene, Mixed Isomers, and Ethylbenzene.

VOLATILE ORGANIC COMPOUNDS

Table with 3 columns: Property (A-E), Value in lb/gal, Value in g/l. Rows include Coating Density, Total Volatiles, Organic Volatiles, Percent Non-Volatile, and Coating VOC (Total) with sub-rows for Material VOC and Solids.

WASTE DISPOSAL

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act(RCRA)40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Addition reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any us of his information.