#68001 - 1 GALLON

SECTION I - MANUFACTURERS INFORMATION

PRODUCT NUMBER:68001PRODUCT NAME:SparkleDATE PREPARED:02.07.1REVISION DATE:06.14.1

Sparkle Silver 02.07.2019 06.14.2019

 COMPANY:
 EXCEL AUTOBODY PRODUCTS

 ADDRESS:
 2921 SYENE ROAD

 CITY:
 MADISON, WI 53713

 PHONE:
 (800) 957-0848

 EMERGENCY PHONE:
 (800) 424-9300

SECTION II - HAZARDOUS INGREDIENTS

| CLASSIFICATION: | |
|--|-----------------|
| Flammable Liquids | Category 3 |
| Skin Corrosion/Irritation | Category 2 |
| Serious Eye Damage/Eye Irritation | Category 2B |
| Acute Toxicity, Inhalation | Category 4 |
| Specific target organ toxicity, single exposure, R | Category 3 |
| Germ Cell Mutagenicity | Category 2 |
| Carcinogenicity | Category 1A, 1B |
| Reproductive Toxicity | Category 2 |
| Specific target organ toxicity, repeated exposure | Category 2 |

SIGNAL WORD: DANGER!



HAZARD STATEMENTS:

- H226 Flammable liquid and vapor
- H315 Causes skin irritation
- H320 Causes eye irritation
- H332 Harmful if inhaled
- H335 May cause respiratory irritation
- H341 Suspected of causing genetic defects
- H350 May cause cancer
- H361 Suspected of damaging fertility or the unborn child
- H373 Causes damage to organs through prolonged or repeated exposure

Excel Products US, Inc., 2921 Syene Rd, Madison, WI 53713 Tel: (800) 957-0848 Fax: (608) 274-5313 Email:marketing@excelproducts.net Website:<u>www.excelproducts.net</u>

Excel Autobody Products

#68001 - 1 GALLON

PRECAUTIONARY STATEMENTS:

| PRECAUTIONARY STA | TEMENTS. |
|---------------------|--|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P210 | Keep away from heat/sparks/open flames/hot surface - No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/light/equipment, etc. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P264 | Wash hands thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated are. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P281 | Use personal protective equipment as required. |
| P302+352 | IF ON SKIN: Wash with soap and water. |
| P303+361+353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if |
| | present and easy to do so - continue rinsing. |
| P308+313 | IF exposed or concerned: get medical advice/attention. |
| P312 | Call a POISON CENTER or a doctor/physician if you feel unwell. |
| P314 | Get medical advice/attention if you feel unwell. |
| P332+313 | If skin irritation occurs: get medical advice/attention. |
| P337+313 | If eye irritation persists get medical advice/attention. |
| P362 | Take off contaminated clothing and wash before reuse. |
| P370+378 | In case of fire: Usedry sand, dry chemical, or alcohol-resistant foam for extinction. |
| P403+233 | Store in a well ventilated place. Keep container tightly closed. |
| P403+235 | Store in a well ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container to an approved waste disposal plant. |
| SECTION III - COMPO | DSITION/INFORMATION ON INGREDIENTS |

SITION/INFORMATION ON

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

| MATERIAL: Isopropyl Alcohol 99% | CAS #: 67 - 63 - 0 | WEIGHT %: 1 - 5 |
|---------------------------------------|-----------------------|--------------------|
| Stoddard Solvent | 8052 - 41 - 3 | 1 - 5 |
| Butyl Acetate | 123 - 86 - 4 | 30 - 35 |
| Propylene Glycol Methyl Ether Acetate | 108 - 65 - 6 | 15 - 20 |
| Dimethylbenzene | 1330 - 20 - 7 | 25 - 30 |

#68001 - 1 GALLON

SEE SECTIONS VIII, XI, XII FOR TOXICOLOGICAL INFORMATION.

SECTION IV - FIRST AID MEASURES

CONTACT WITH EYES: Flush IMMEDIATELY with copious amounts of running water for at least 15 minutes. Take to physician for definitive medical treatment.

SKIN CONTACT: Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, consult a physician.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

INGESTION: If swallowed. Do not induce vomiting. Seek immediate medical attention.

SECTION V - FIREFIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Water fog, foam, dry chemical, or carbon dioxide extinguisher.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

Excel Autobody Products

UNUSUAL FIRE FIGHTING HAZARDS: Vapor accumulation will flash and/or explode, if ignited. Containers may burst explosively if overheated in fire. Cool with water spray or fog. Empty containers also present fire explosion hazard due to residual vapors. Keep containers tightly closed. During emergency situations, over-exposure to decomposition products may cause a health hazard with no symptoms immediately apparent. Obtain medical attention.

SECTION VI - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Keep all sources of ignition and hot metal surfaces away from spill or release.

ENVIRONMENTAL PRECAUTIONS: Contain spill if it can be done with minimal risk. Prevent liquid from entering drains, sewers or waterways. Notify proper authorities if spill is in excess of the reportable quantity.

METHODS FOR CLEANING UP. Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container. Call Chemtrec at 1-800-424-9300 (CCN16851) for additional information.

SECTION VII - HANDLING AND STORAGE

HANDLING AND STORAGE: "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources. Keep containers tightly closed when not in use. Store out of direct sunlight and in a cool, well-ventilated area.

#68001 - 1 GALLON

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

| EXPOSURE LIMITS: | | | |
|---------------------------------------|-----------------------|----------------------|-----------------------------|
| MATERIAL: Isopropyl Alcohol 99% | CAS #: 67 - 63 - 0 | OSHA PEL: 400 ppm | ACGIH TLV: 200 ppm (TWA) |
| Stoddard Solvent | 8052 - 41 - 3 | 500 ppm | 100 ppm |
| Butyl Acetate | 123 - 86 - 4 | 150 ppm | 150 ppm |
| Propylene Glycol Methyl Ether Acetate | 108 - 65 - 6 | Not Established | Not Established |
| Dimethylbenzene | 1330 - 20 - 7 | 100 ppm | 100 ppm |
| | | | |

ENGINEERING CONTROLS: Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV.

MONITORING: Follow accepted work practices for handling a flammable material.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE PROTECTION: Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product. SKIN PROTECTION: Impervious solvent resistent gloves. Impervious apron and work boots recommend where splashing may occur. RESPIRATORY PROTECTION: Use NIOSH/MSHA TC23C Chemical/Mechanical type filter system to remove a combination of particles, gas & vapors or air supplied respirator if necessary in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

| APPEARANCE: ODOR: ODOR THRESHOLD: pH@25°C: MELTING/FREEZING POINT: FLASHPOINT: SPECIFIC GRAVITY (water=1): WATER SOLUBILITY: AUTO-IGNITION TEMPERATURE: DECOMPOSITION TEMPERATURE: BOILING RANGE: EVAPORATION RATE: LOWER FLAMMABLE LIMIT: UPPER FLAMMABLE LIMIT: VAPOR PRESSURE: VAPOR DENSITY (air=1): | Silver Mild Not Available Not Applicable Not Available .96 Negligible Not Available Not Available -°F Slower than Ether 1% 7% 0mm Hg@68°F >1.0 |
|---|--|
| | 0mm Hg@68°F |
| | |

Excel Products US, Inc., 2921 Syene Rd, Madison, WI 53713 Tel: (800) 957-0848 Fax: (608) 274-5313 Email:marketing@excelproducts.net Website:<u>www.excelproducts.net</u>

Excel Autobody Products

SPARKLE SILVER

#68001 - 1 GALLON

SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions of storage and handling.

CONDITIONS TO AVOID: Heat, open flames, ignition sources, electrical or static discharge.

HAZARDOUS DECOMPOSITION/BYPRODUCTS: CO2 and possibly CO and carbon smoke.

HAZARDOUS POLYMERIZATION: Will not occur.

POLYMERIZATION CONDITIONS TO AVOID: None.

INCOMPATIBILITIES: None known.

SECTION XI - TOXICOLOGICAL INFORMATION

LIKELY ROUTE OF EXPOSURE: Inhalation, eye contact, skin contact, ingestion.

INHALATION: Anesthetic. Irritation of respiratory tract or acute nervous system depression.

Overexposure may result in headaches and nausea possibly followed by loss of consciousness.

EYE CONTACT: High vapor concentrations are irritating to the eyes.

SKIN CONTACT: Liquids can be absorbed through the skin resulting in symptoms similar to the inhalation effects above.

INGESTION: Gastrointestinal irritation including vomiting can occur. Aspiration of material into lungs may result in chemical pneumonitis, which can be fatal.

TOXICITY: MATERIAL: Isopropyl Alcohol 99%

Stoddard Solvent Butyl Acetate Propylene Glycol Methyl Ether Acetate Dimethylbenzene LD50: Dermal: 16,400 mg/kg (rabbit) Oral: 5,840 mg/kg (rat) Not Established Oral: 7,100 mg/kg (mouse) Dermal: >5,000 mg/kg (rabbit) Oral: 8,532 mg/kg (rat) Dermal: 4,500 mg/kg (rabbit) Oral: 2,840 mg/kg (rat)

LC50: Inhalation: 8 h 1,600 ppm (rat)

Not Established Inhalation: 2,000 ppm Not Established

Inhalation: 4 h 6,350 mg/l (rat)

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section XI (Tocicological Information) for further data on the effects of this product's components on test animals.

MOBILITY: This material is a mobile liquid.

DEGRADABILITY: This product is completely biodegradable.

BIOACCUMULATION: This product does not accumulate or biomagnify in the environment.

Excel Products US, Inc., 2921 Syene Rd, Madison, WI 53713 Tel: (800) 957-0848 Fax: (608) 274-5313 Email:marketing@excelproducts.net Website:<u>www.excelproducts.net</u>

#68001 - 1 GALLON

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Do not discharge into drains, surface water, or groundwater. Empty containers can retain product residue and vapor. Observe all precautions even when containers are empty. The use and processing of this product, or addition of other constituents, may cuase it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA. Dispose of or incinerate in accordance with all applicable local, state, and federal regulations at a RCRA licensed facility.

SECTION XIV - TRANSPORT INFORMATION

| US GROUND (DOT) SHIPPING INFORM | IATION: |
|---------------------------------|---------|
| UN NUMBER: | UN1263 |
| PROPER SHIPPING NAME: | PAINT |
| TRANSPORT HAZARD CLASS: | 3 |
| PACKAGING GROUP. | 111 |

OTHER SHIPPING INFORMATION: With inner packagings containing 5 liters (1.32 gallons) or less, this product may be shipped as Limited Quantity. Any containers containing more than 5 liters may be shipped as: UN1263, PAINT, 3, PG III.

SECTION XV - REGULATORY INFORMATION

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

| ACUTE: Yes | CHRONIC: No | FIRE: Yes | PRESSURE: No | REACTIVE: No | |
|---|----------------|--------------|--|--------------------------------|-------------------------|
| SARA TITLE III COMPONENT I Butyl Acetate Dimethylbenze | | INFORMATION: | CAS #: 123 - 86 - 4 1330 - 20 - 7 | % BY WT. 30 - 35 25 - 30 | |
| CERCLA SECTI COMPONENT N Butyl Acetate Dimethylbenze | | SUBSTANCE: | 1330-20-7 CAS #: 123 - 86 - 4 1330 - 20 - 7 | % BY WT. 30 - 35 25 - 30 | RQ(LBS.) 5000 100 |

CALIFORNIA PROPOSITION 65:

WARNING! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov

SECTION XVI - OTHER INFORMATION

| HMIS Health: | 2 |
|--------------------|---|
| HMIS Flammability: | 3 |
| HMIS Reactivity: | 0 |

DISCLAIMER: WARNING! KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN! The information contained in this SDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, or fire prevention as necessary or appropriate to use and understand the data in this SDS.

Excel Products US, Inc., 2921 Syene Rd, Madison, WI 53713 Tel: (800) 957-0848 Fax: (608) 274-5313 Email:marketing@excelproducts.net Website:<u>www.excelproducts.net</u>