

# ACRYLIC PRIMER - GRAY

#33001-1 GALLON



## SECTION I - MANUFACTURERS INFORMATION

PRODUCT NUMBER: 33001  
 PRODUCT NAME: Acrylic Primer - Gray  
 DATE PREPARED: 02.07.2019  
 REVISION DATE: 06.14.2019

COMPANY: EXCEL AUTOBODY PRODUCTS  
 ADDRESS: 2921 SYENE ROAD  
 CITY: MADISON, WI 53713  
 PHONE: (800) 957-0848  
 EMERGENCY PHONE: (800) 424-9300

## SECTION II - HAZARDOUS INGREDIENTS

CLASSIFICATION:	
Flammable Liquids	Category 3
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2B
Acute Toxicity, Inhalation	Category 4
Specific target organ toxicity, single exposure, R	Category 3
Germ Cell Mutagenicity	Category 2
Carcinogenicity	Category 1A, 1B
Reproductive Toxicity	Category 2
Specific target organ toxicity, repeated exposure	Category 2

SIGNAL WORD: **DANGER!**

PICTOGRAMS:



## HAZARD STATEMENTS:

H226	Flammable liquid and vapor
H315	Causes skin irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H373	Causes damage to organs through prolonged or repeated exposure

Excel Products US, Inc.,  
 2921 Syene Rd, Madison, WI 53713  
 Tel: (800) 957-0848 Fax: (608) 274-5313  
 Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)  
 Website: [www.excelproducts.net](http://www.excelproducts.net)

# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

**PRECAUTIONARY STATEMENTS:**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surface - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated are.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P302+352	IF ON SKIN: Wash with soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.
P308+313	IF exposed or concerned: get medical advice/attention.
P312	Call a POISON CENTER or a doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P332+313	If skin irritation occurs: get medical advice/attention.
P337+313	If eye irritation persists get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370+378	In case of fire: Usedry sand, dry chemical, or alcohol-resistant foam for extinction.
P403+233	Store in a well ventilated place. Keep container tightly closed.
P403+235	Store in a well ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to an approved waste disposal plant.

**SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS**

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

MATERIAL:	CAS #:	WEIGHT %:
Talc	14807-96-6	20-40
Acetone	67-64-1	5-15
Glycol Ether PM Acetate	108-65-6	5-15
Parachlorobenzotrifluoride	98-56-6	5-15
Titanium Dioxide	13463-67-7	5-15
Tremolite (Non-asbestiform)	14567-73-8	5-15
Xylene	1330-20-7	5-15
Aluminum Hydroxide Regulatory	21645-51-2	0-5
Carbon Black	1333-86-4	0-5
Crystalline Quartz Regulatory	14808-60-7	0-5
Dibutyltin Dilaurate	77-58-7	0-5
Ethylbenzene	100-41-4	N/A
Methyl n-Amyl Ketone	110-43-0	N/A
Phosphoric Acid Regulatory	7664-38-2	0-5
Silica	7631-86-9	0-5
Toluene	108-88-3	0-5

Excel Products US, Inc.,

2921 Syene Rd, Madison, WI 53713

Tel: (800) 957-0848 Fax: (608) 274-5313

Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)Website: [www.excelproducts.net](http://www.excelproducts.net)

# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

SEE SECTIONS VIII, XI, XII FOR TOXICOLOGICAL INFORMATION.

## SECTION IV - FIRST AID MEASURES

**CONTACT WITH EYES:** Flush IMMEDIATELY with copious amounts of running water for at least 15 minutes. Take to physician for definitive medical treatment.

**SKIN CONTACT:** Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, consult a physician.

**INHALATION:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.

**INGESTION:** If swallowed. Do not induce vomiting. Seek immediate medical attention.

## SECTION V - FIREFIGHTING MEASURES

**SUITABLE EXTINGUISHING MEDIA:** Water fog, foam, dry chemical, or carbon dioxide extinguisher.

**SPECIAL FIRE FIGHTING PROCEDURES:** Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

**UNUSUAL FIRE FIGHTING HAZARDS:** Vapor accumulation will flash and/or explode, if ignited. Containers may burst explosively if overheated in fire. Cool with water spray or fog. Empty containers also present fire explosion hazard due to residual vapors. Keep containers tightly closed. During emergency situations, over-exposure to decomposition products may cause a health hazard with no symptoms immediately apparent. Obtain medical attention.

## SECTION VI - ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS:** Keep all sources of ignition and hot metal surfaces away from spill or release.

**ENVIRONMENTAL PRECAUTIONS:** Contain spill if it can be done with minimal risk. Prevent liquid from entering drains, sewers or waterways. Notify proper authorities if spill is in excess of the reportable quantity.

**METHODS FOR CLEANING UP:** Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container. Call Chemtrec at 1-800-424-9300 (CCN16851) for additional information.

## SECTION VII - HANDLING AND STORAGE

**HANDLING AND STORAGE:** "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources. Keep containers tightly closed when not in use. Store out of direct sunlight and in a cool, well-ventilated area.

# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

## SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

US. OSHA Specifically Regulated Substances (29 CFR 1910. 1001-1050)

Material:	CAS :	Type:	Value:
Tremolite (Non-asbestiform)	14567-73-8	STEL TWA	1 fibers/cm3 0.1 fibers/cm3

US. OSHA Table -1 Limits for Air Contaminants (29 CFR 1910,1000)

Material:	CAS #:	Type:	Value:	Form:
Acetone	67-64-1	PEL	2400 mg/m3, 1000 ppm	
Carbon Black	1333-86-4	PEL	3.5 mg/m3	
Dibutyltin Dilaurate	77-58-7	PEL	0.1 mg/m3	
Ethylbenzene	100-41-4	PEL	435 mg/m3	
Methyl n-Amyl Ketone	110-43-0	PEL	465 mg/m3, 100 ppm	
Phosphoric Acid Regulatory	7664-38-2	PEL	1 mg/m3, 100 ppm	
Titanium Dioxide	13463-67-7	PEL	15mg/m3	Total dust.
Xylene	1330-20-7	PEL	435 mg/m3, 100 ppm	

US. OSHA Table -2 (29 CFR 1910,1000)

Material:	CAS #:	Type:	Value:
Toluene	108-88-3	Ceiling TWA	300ppm 200ppm

US. OSHA Table -3 (29 CFR 1910,1000)

Material:	CAS :	Type:	Value	Form:
Crystalline Quartz Regulatory	14808-60-7	TWA	0.3 mg/m3	Total dust.
			0.1 mg/m3, 2.4 mppcf	Respirable
Silica	7631-86-9	TWA	0.8 mg/m3, 20 mpccf	
Talc	14807-96-6	TWA	0.3mg/m3 20 mppcf 2.4 mppcf	Total dust. Respirable. Respirable.

US. ACGIH Threshold Limit Values

Material:	CAS #:	Type:	Value:	Form:
Acetone	67-64-1	STEL TWA	750 ppm 500 ppm	
Aluminum Hydroxide Regulatory	21645-51-2	TWA	1 mg/m3	Respirable fraction
Carbon Black	1333-86-4	TWA	3mg/m3	Inhalable fraction
Crystalline Quartz Regulatory	14808-60-7	TWA	0.025 mg/m3	Respirable fraction
Dibutyltin Dilaurate	77-58-7	STEL TWA	0.2 mg/m3 0.1 mg/m3	
Ethylbenzene	100-41-4	TWA	20 ppm	
Methyl n-Amyl Ketone	110-43-0	TWA	50 ppm	
Phosphoric Acid Regulatory	7664-38-2	STEL TWA	3 mg/m3 1 mg/m3	
Talc	14807-96-6	TWA	2 mg/m3	Respirable fraction
Titanium Dioxide	13463-67-7	TWA	10 mg/m3	
Toluene	108-88-3	TWA	20 ppm	
Trmolite	14567-73-8	TWA	0.1 fibers/cm3	Fiber
Xylene	1330-20-7	STEL TWA	150 ppm 100 ppm	

Excel Products US, Inc.,

2921 Syene Rd, Madison, WI 53713

Tel: (800) 957-0848 Fax: (608) 274-5313

Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)Website: [www.excelproducts.net](http://www.excelproducts.net)



# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

US. NIOSH: Pocket Guide to Chemical Hazards

Material:	CAS #:	Type:	Value:	Form:
Acetone	67-64-1	TWA	50 mg/m3, 250 ppm	
Carbon Black	1333-86-4	TWA	0.1 mg/m3	
Crystalline Quartz Regulatory	14808-60-7	TWA	0.05 mg/m3	Respirable dust.
Dibutyltin Dilaurate	77-58-7	TWA	0.1 mg/m3	
Ethylbenzene	100-41-4	STEL	545 mg/m3, 125 ppm	
Methyl n-Amyl Ketone	110-43-0	TWA	435 mg/m3, 100 ppm	
Phosphoric Acid Regulatory	7664-38-2	TWA	465 mg/m3, 100 ppm	
		STEL	3 mg, m3	
Silica	7631-86-9	TWA	1 mg/m3	
Talc	14807-96-6	TWA	6 mg/m3	Respirable.
Toluene	108-88-3	TWA	2mg/m3	
		STEL	560 mg/m3, 150 ppm	
		TWA	375 mg/m3, 100 ppm	

## US. workplace Environmental Exposure Level (WEEL) Guidelines

Material:	CAS #:	Type:	Value:
Glycol Ether PM Acetate	108-65-6	TWA	50 ppm

## 4[a^a]US^>L [fHS^gW

## 359;: 4[a^a]US^7j baegdW^ V[UW

B Vi ZgVahv	KVaj Z	9ZiZgb ^cVci°	HeZX^b Zc°
Acetone	50 mg/l	Acetone	Urine
: i] naVZcoZcZ	%#* ^\\$	Hj b °d[°b VcYZaX^VXZYXfi°e] Zcna^andmaX^VX^Y	8gZVi ^c^cZ^°c^j gtcZ
I daj ZcZ	%# b \ \$	d°8gzhda°l ^] °nYgdlah°h	8gZVi ^c^cZ^°c^j gtcZ
	%#( b \ \$a	I daj ZcZ	J gtcZ
	%#% b \ \$a	I daj ZcZ	7aldY
MhZcZ	&# ^\\$ °	B Zi] na°eej gX^VX^Yh	CgZVi ^c^cZ^°c^j gtc

Z[dghVb eac° YZiV^hl°eZVhZ hZZ°i] Z°hdj gZ

## : nedhj gZ°<j ^YZ^acZh

### J #H°°8Va[dc°VD: Ah/H ^c^YZh^cVi ^dc

9^Vj tyltin Dilaurate	Can be absorbed through the skin.
Glycol Ether PM Acetate	Can be absorbed through the skin
Toluene	Can be absorbed through the skin

### J #H°° Minnesota Haz Subs/H ^c^YZh^cVi ^dc applies

9^Vj tyltin Dilaurate	Skin Designation applies.
Toluene	Skin Designation applies.

### J #H°° Tennessee OELs/H ^c^YZh^cVi ^dc

9^Vj tyltin Dilaurate	Can be absorbed through the skin.
-----------------------	-----------------------------------

### J #H°°ACGIH Threshold Limit Values: Skin Designation

9^Vj tyltin Dilaurate	Can be absorbed through the skin.
-----------------------	-----------------------------------

### J #H°°NIOSH Pocket Guide to Chemeical Hazards/H ^c^YZh^cVi ^dc

9^Vj tyltin Dilaurate	Can be absorbed through the skin.
-----------------------	-----------------------------------



# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

**ENGINEERING CONTROLS:** Explosion-proof general and local exhaust ventilation.

Good general ventilation should be used ( typically 10 air changes per hour). Match ventilation rates to conditions. If Applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**MONITORING:** Follow accepted work practices for handling a flammable material.

**PERSONAL PROTECTIVE EQUIPMENT (PPE)**

**EYE PROTECTION:** chemical respirator with organic vapor cartridge and full facepiece

**SKIN PROTECTION:** wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**RESPIRATORY PROTECTION:** Chemical respirator with organic vapor cartridge and full facepiece

**Thermal Hazards:** Wear appropriate thermal protective clothing, when necessary.

**General Hygiene Considerations:** when using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Gray
ODOR:	Not Available
ODOR THRESHOLD:	Not Available
pH@25°C:	-138.46°F (-94.7°C)
MELTING/FREEZING POINT:	132.89°F(56.05°C)
Initial Boiling Point and Range:	-4.0°F(-20.0°C)
FLASHPOINT:	
SPECIFIC GRAVITY (water=1):	1.23
WATER SOLUBILITY:	Negligible
AUTO-IGNITION TEMPERATURE:	869°F (465°C) estimated
DECOMPOSITION TEMPERATURE:	Not Available
BOILING RANGE:	134.24°F
EVAPORATION RATE:	Not Available
FLAMMABILITY CLASS:	Flammable IB estimated
LOWER FLAMMABLE LIMIT:	N/A
UPPER FLAMMABLE LIMIT:	12.8%
LOWER EXPLOSIVE LIMIT:	Not Available
UPPER EXPLOSIVE LIMIT:	Not Available
VAPOR PRESSURE:	Not Available
VAPOR DENSITY (air=1):	Not Available
DENSITY :	2.06 g/cm <sup>3</sup>
PERCENT VOLATILE:	33.01 w/w % By Weight 52.26 v/v % By Volume
SPECIFIC GRAVITY :	2.06
VOC (Weight%)	1.59 lb/gal (Actual VOC-With Water With Exempts) 2.30 lb/gal (Regulatory VOC-Less Water Less Exempts) 190.71 g/L (Actual VOC-With Water With Exempts) 275.96g/L (Regulatory VOC-Less Water Less Exempts)



# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

## SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions of storage and handling.

CONDITIONS TO AVOID: Heat, open flames, ignition sources, electrical or static discharge.

HAZARDOUS DECOMPOSITION/BYPRODUCTS: CO<sub>2</sub> and possibly CO and carbon smoke.

HAZARDOUS POLYMERIZATION: Will not occur.

POLYMERIZATION CONDITIONS TO AVOID: None.

INCOMPATIBILITIES: None known.

## SECTION XI - TOXICOLOGICAL INFORMATION

LIKELY ROUTE OF EXPOSURE: Inhalation, eye contact, skin contact, ingestion.

INHALATION: Anesthetic. Irritation of respiratory tract or acute nervous system depression.

Overexposure may result in headaches and nausea possibly followed by loss of consciousness.

EYE CONTACT: High vapor concentrations are irritating to the eyes.

SKIN CONTACT: Liquids can be absorbed through the skin resulting in symptoms similar to the inhalation effects above.

INGESTION: Gastrointestinal irritation including vomiting can occur. Aspiration of material into lungs may result in chemical pneumonitis, which can be fatal.

### TOXICITY:

MATERIAL:	LD50:	LC50:
Acetone	Dermal: 20,000 mg/kg (Rabbit) Oral: 3,000 mg/kg (Mouse) 5,340 mg/kg (Rabbit) 5,800 mg/kg (Rat)	Inhalation: 20 mg/kg, 76 mg/l, 4 hours (Rat)
Aluminum Hydroxide Regulatory	Oral: >5,000 mg/kg (Rat)	
Carbon Black	Oral: >8,000 (Rat)	
Dibutyltin Dialurate	Oral: 175 mg/kg (Rat)	
Ethylbenzene	Dermal: 17,800 mg/kg (Rabbit) Oral: 3,500 mg/kg (Rat)	
Methyl n- Amyl Ketone	Dermal: 12,600 mg/kg (Rabbit) Oral: 730 mg/kg (Mouse) 1.67 (g/kg)	
Phosphoric Acid Regulatory	Dermal: 2,740 mg/kg (Rabbit) Oral: 1,530 mg/kg (Rat)	
Silica	Oral: >15000 mg/kg (Mouse) >22,500 mg/kg (Rat)	
Toluene	Dermal: 12124 mg/kg, 14.1 ml/kg (Rabbit) Oral: 2.6 g/kg (Rat)	Inhalation: 5320 ppm, 8 hours (Mouse) 400 ppm 24 hours (Mouse) 26,700 ppm, 1 hour (Rat) 12,200 ppm, 2 hours (Rat) 8000 ppm, 4 hours (Rat)
Xylene	Dermal: >43 g/kg (Rabbit) Oral: 1590 mg/kg (Mouse) 3523-8600 mg/kg (Rat)	Inhalation: 3907 mg/l, 6 hours (Mouse) Inhalation: 6350 mg/l, 4 hours (Rat)

Skin Irritation:

Causes skin Irritation.

Eye Irritation:

Causes serious eye irritation.

Respiratory Sensitization:

Not a respiratory sensitizer.

Skin Sensitization:

This product is not expected to cause skin sensitization.

Germ Cell Mutagenicity:

No data available to indicate product or any components present at greater than

0.1% are mutagenic or genotoxic

Excel Products US, Inc.,

2921 Syene Rd, Madison, WI 53713

Tel: (800) 957-0848 Fax: (608) 274-5313

Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)Website: [www.excelproducts.net](http://www.excelproducts.net)



# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

**Carcinogenicity:** May cause cancer

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4)

Crystalline Quartz Regulatory (CAS 14808-60-7)

Ethylbenzene (CAS 100-41-4)

Silica (CAS 7631-86-9)

Titanium Dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Xylene (CAS 1330-20-7)

2B Possible Carcinogenic to humans.

1 Carcinogenic to humans.

2B Possible carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

1 Carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Temolite (Non-asbestiform) (CAS 14567-73-8)

Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline Quartz Regulatory (CAS 14808-60-7)

Known To Be Human Carcinogen

Temolite (Non-asbestiform) (CAS 14567-73-8)

Known To Be Human Carcinogen

Reproductive Toxicity

Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child

Specific Target Organ Toxicity - Exposure

Not classified, single

Specific Target Organ Toxicity - Exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration Hazard

Not an aspiration hazard.

Chronic Effects

Causes damage to organs through prolonged or repeated exposure  
Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## SECTION XII - ECOLOGICAL INFORMATION (Harmful to aquatic life with long lasting effects)

Material:	CAS #	EC50:	LC50:
Acetone	67-64-1	Crustacea: Water Flea (Daphnia Magna) 10294-17704 mg/l, 48 hours	Fish: Rainbow Trout, Donaldson Trout (Oncorhynchus Mykiss) 4740-6330 mg/l, 96 hours
Ethylbenzene	100-41-4	Crustacea: Water Flea (Daphnia Magna) 1.37-4.4 mg/l, 48 hours	Fish: Flathead Minow (Pimephales Promelas) 126-137 mg/l, 96 hours
Methyl n-Amyl Ketone	110-43-0	N/A	Fish: Flathead Minow (Pimephales Promelas) 126-137 mg/l, 96 hours
Titanium Dioxide	13463-67-7	Crustacea: Water Flea (Daphnia Magna) >1,000 mg/l, 48 hours	Fish: Mummichog (Fundulus Heteroclitus) >1,000 mg/l, 96 hours
Toluene	108-88-3	Crustacea: Water Flea (Daphnia Magna) 5.46-9.83 mg/l, 48 hours	Fish: Coho Salmon Silver Salmon (Oncorhynchus Kisutch) 8.11 mg/l, 96 hours
Xylene	1330-20-7	N/A	Fish: Bluegill (Lepomis Macrochirus) 7.711-9.591 mg/l, 96 hours

Excel Products US, Inc.,

2921 Syene Rd, Madison, WI 53713

Tel: (800) 957-0848 Fax: (608) 274-5313

Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)

Website: [www.excelproducts.net](http://www.excelproducts.net)



# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

Persistence and Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential:

Partition coefficient n-octanol/ water (log Kow)

Acetone	-0.24
Dibutyltin Dilaurate	3.12
Ethylbenzene	3.15
Methyl n-Amyl Ketone	1.98
Toluene	2.73
Xylene	3.12-3.2

Mobility in Soil: No data available

Other Adverse Effects: No other adverse environmental effect (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

**Disposal Instructions:** collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local Disposal Regulations:** Dispose in accordance with all applicable regulations.

**Hazardous Waste Code:** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste From Residues/ Unused Products:** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated Packaging:** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## SECTION XIV - TRANSPORT INFORMATION

US GROUND (DOT) SHIPPING INFORMATION:

UN NUMBER:	UN1263
PROPER SHIPPING NAME:	Paint related material including paint thinning, dyeing, removing, or reducing compound.
TRANSPORT HAZARD CLASS:	3
SUBSIDIARY RISK:	-
LABEL(S):	3
PACKAGING GROUP:	II

US GROUND (IATA) SHIPPING INFORMATION:

UN NUMBER:	UN1263
PROPER SHIPPING NAME:	Paint related material including paint thinning, dyeing, removing, or reducing compound.
TRANSPORT HAZARD CLASS:	3
SUBSIDIARY RISK:	-
PACKAGING GROUP:	II
ENVIRONMENTAL HAZARDS:	No
ERG CODE:	3L

Special Precautions for user: Read safety instructions, SDS and emergency procedures before handling.

Passenger and Cargo Aircraft: Allowed

Cargo Aircraft Only: Allowed

Excel Products US, Inc.,

2921 Syene Rd, Madison, WI 53713

Tel: (800) 957-0848 Fax: (608) 274-5313

Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)

Website: [www.excelproducts.net](http://www.excelproducts.net)

# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

**US GROUND (IMDG) SHIPPING INFORMATION:**

UN NUMBER: UN1263  
 PROPER SHIPPING NAME: Paint (Including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or paint related material (Including paint thinnig or reducing compound)  
 TRANSPORT HAZARD CLASS: 3  
 SUBSIDIARY RISK: -  
 PACKAGING GROUP: II  
 ENVIROMENTAL HAZARDS: No  
 EmS: F-E,S-E

Special precaution for user: Read safety instructions, SDS and emergency prodedures begore handling.  
 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not Established

OTHER SHIPPING INFORMATION: With inner packagings containing 5 liters (1.32 gallons) or less, this product may be shipped as Limited Quantity. Any containers containing more than 5 liters may be shipped as: UN1263, PAINT, 3, PG III. (Transportation Informationo is proveded based on the manugacturer's interptation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

**SECTION XV - REGULATORY INFORMATION**

US Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200

TSCA Section 12(b0 Export Notification (40 CFR 707, Subpt. D)

Tremolite (Non-asbestiform)(CAS 14567-73-8)	0.1% Annual Export Notification required
CERCLA Hazardous Substance List (40 CFR 302.4)	
Acetone (CAS 67-64-1)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Phosphoric Acid Regulatory (CAS 7664-38-2)	Listed.
Toluene (CAS 108-88-3)	Listed.
Tremolite (Non-asbestiform) (CAS 14567-73-8)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification  
 Not Regulated

OSHA specifically Regulated Substances (29 CFR 1910.1001-1050)  
 Tremolit (Non-asbestiform) (CAS 14567-73-8) Lung Cancer

Syperfund Amedmetns and Reauthorization Act of 1986 (SARA)  
 Hazard Categoriess: Immediate Hazard-Yes  
 Delayed Hazard-Yes  
 Fire Hazard-Yes  
 Pressure Hazard-No  
 Reactivity Hazard-No

SARA 302 Extremely hazardous substance  
 Not listed

SARA 311/312 Hazardous  
 No Chemical

SARA TITLE SECTION 313 (TRI reporting):

MATERIAL:	CAS #:	% BY WT.
Tremolite (Non-asbestiform)	14567-73-8	5-15
Xylene	1330 - 20 - 7	5-15
Ethylbenzene	100-41-4	n/a
Toluene	108-88-3	0-5

Excel Products US, Inc.,

2921 Syene Rd, Madison, WI 53713

Tel: (800) 957-0848 Fax: (608) 274-5313

Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)

Website: [www.excelproducts.net](http://www.excelproducts.net)



# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)  
Toluene (CAS 108-88-3)  
Tremolite (Non-asbestiform) (CAS 14567-73-8)  
Xylene (CAS 1330-20-7)

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated

## Safe Drinking Water Act (SDWA)

Not regulated

## Drug Enforcement Administration (DEA)

## List 2, Essential Chemical (21 CFR 1310.02(b)) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	6594

## List 1 & 2, Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)	35%WV
Toluene (CAS 108-88-3)	35%WV

## Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	594



# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

## US. State Regulations

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not Listed

**US. California Candidate Chemicals List. Safer consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3 sub'd (a))**

Acetone (CAS 67-64-1)  
Carbon Black (CAS 1333-86-4)  
Crystalline Quartz Regulatory (CAS 14808-60-7)  
Ethylbenzene (CAS 100-41-4)  
Phosphoric Acid Regulatory (CAS 7664-38-2)  
Talc (CAS 14807-96-6)  
Titanium Dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Tremolite (Non-asbestiform) (CAS 14567-73-8)  
Xylene (CAS 1330-20-7)

## US. Massachutes RTK-Substance List

Acetone (CAS 67-64-1)  
Carbon Black (CAS 1333-86-4)  
Crystalline Quartz Regulatory (CAS 14808-60-7)  
Ethylbenzene (CAS 100-41-4)  
Phosphoric Acid Regulatory (CAS 7664-38-2)  
Talc (CAS 14807-96-6)  
Titanium Dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Tremolite (Non-asbestiform) (CAS 14567-73-8)  
Xylene (CAS 1330-20-7)

## US. New Jersey Worker and Community Right-to-Know Act.

Acetone (CAS 67-64-1)  
Carbon Black (CAS 1333-86-4)  
Crystalline Quartz Regulatory (CAS 14808-60-7)  
Ethylbenzene (CAS 100-41-4)  
Phosphoric Acid Regulatory (CAS 7664-38-2)  
Talc (CAS 14807-96-6)  
Titanium Dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Tremolite (Non-asbestiform) (CAS 14567-73-8)  
Xylene (CAS 1330-20-7)

## US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)  
Carbon Black (CAS 1333-86-4)  
Crystalline Quartz Regulatory (CAS 14808-60-7)  
Ethylbenzene (CAS 100-41-4)  
Phosphoric Acid Regulatory (CAS 7664-38-2)  
Talc (CAS 14807-96-6)  
Titanium Dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Tremolite (Non-asbestiform) (CAS 14567-73-8)  
Xylene (CAS 1330-20-7)

Excel Products US, Inc.,

2921 Syene Rd, Madison, WI 53713

Tel: (800) 957-0848 Fax: (608) 274-5313

Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)

Website: [www.excelproducts.net](http://www.excelproducts.net)



# ACRYLIC PRIMER - GRAY

#33001-1 GALLON

## US. Rhode Island RTK

Acetone (CAS 67-64-1)  
 Ethylbenzene (CAS 100-41-4)  
 Phosphoric Acid Regulatory (CAS 7664-38-2)  
 Tremolite (Non-asbestiform) (CAS 14567-73-8)  
 Toulene (CAS 108-88-3)  
 Xylene (CAS 1330-20-7)

## US. - California Proposition 65 - CRT: Listed date/Carcinogenic Substance

Carbon Black (CAS 1333-86-4)	Listed: February 21, 2003
Crystalline Quarts Regulatory (CAS 14808-60-7)	Listed: October 1, 1988
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
Titanium Dioxide (CAS 13463-67-7)	Listed: September 2, 2011
Tremolite (Non-asbestiform) (CAS 14567-73-8)	Listed: February 27, 1987

## US. - California Proposition 65 - CRT: Listed date/Developmental Toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

## US. - California Proposition 65 - CRT: Listed date/Female Reproductive Toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

## INTERNATIONAL INVENTORIES

Country or Region	Inventory Name	On Inventory (Yes/No)
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemical and Chemical Substances (PICCS)	No
	United States & Puerto Rico Toxic Substances Control Act (TSCA)	No

A "Yes" indicates that all component of this product comply with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the products are not listed or exempt from listing on the inventory administered by the governing country(s)

### CALIFORNIA PROPOSITION 65:

This product contains no chemicals known to the state of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)

### SECTION XVI - OTHER INFORMATION

HMIS Health: 2  
 HMIS Flammability: 3  
 HMIS Reactivity: 0

DISCLAIMER: WARNING! KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN! The information contained in this SDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, or fire prevention as necessary or appropriate to use and understand the data in this SDS.

Excel Products US, Inc.,  
 2921 Syene Rd, Madison, WI 53713  
 Tel: (800) 957-0848 Fax: (608) 274-5313  
 Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)  
 Website: [www.excelproducts.net](http://www.excelproducts.net)