

**CLASSIC HOT ROD BLACK ACTIVATORY SLOW**

#50204 - 1 QUART

**SECTION I - MANUFACTURERS INFORMATION**

PRODUCT NUMBER: 50204  
PRODUCT NAME: Crystal Clear  
DATE PREPARED: 02.07.2019  
REVISION DATE: 06.14.2019

COMPANY: EXCEL AUTOBODY PRODUCTS  
ADDRESS: 2921 SYENE ROAD  
CITY: MADISON, WI 53713  
PHONE: (800) 957-0848  
EMERGENCY PHONE: (800) 424-9300

**SECTION II - HAZARDOUS INGREDIENTS**

## CLASSIFICATION:

Flammable Liquids	Category 3
Acute toxicity, oral	Category 4
Acute toxicity, dermal	Category 4
Acute toxicity, inhalation	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Sensitization, respiratory	Category 1
Sensitization, skin	Category 1
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
Specific target organ toxicity, repeated exposure	Category 1
Hazardous to the aquatic environment, (acute hazard)	Category 2
Hazardous to the aquatic environment, (long - term hazard)	Category 2
OSHA defined hazards	Not Classified

SIGNAL WORD: **DANGER!**

PICTOGRAMS:

**HAZARD STATEMENTS:**

H226	Flammable liquid and vapor
H315	Causes skin irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H373	Causes damage to organs through prolonged or repeated exposure

Excel Products US, Inc.,  
2921 Syene Rd, Madison, WI 53713  
Tel: (800) 957-0848 Fax: (608) 274-5313  
Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)  
Website: [www.excelproducts.net](http://www.excelproducts.net)



# CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

## PRECAUTIONARY STATEMENTS:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surface - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P302+352	IF ON SKIN: Wash with soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.
P308+313	IF exposed or concerned: get medical advice/attention.
P312	Call a POISON CENTER or a doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P332+313	If skin irritation occurs: get medical advice/attention.
P337+313	If eye irritation persists get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370+378	In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction.
P403+233	Store in a well ventilated place. Keep container tightly closed.
P403+235	Store in a well ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to an approved waste disposal plant.

## SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

MATERIAL:	CAS #:	WEIGHT %:
Hexamethylene Diisocyanate	28182-81-2	30-50
Trimethyl Benzene	25551-13-7	5-20
Trimethyl Benzene	95-63-6	5-20
Xylene	1330-20-7	5-20
2-Butoxyethylacetate	112-07-2	5-15
Glycol Ether PM Acetate	108-65-6	5-15
Butyl Cellosolve/Glycol Ether EB	111-76-2	0-5
Ethylbenzene	100-41-2	n/a
Isopropyl Benzene	98-82-8	n/a

# CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

SEE SECTIONS VIII, XI, XII FOR TOXICOLOGICAL INFORMATION.

## SECTION IV - FIRST AID MEASURES

**SKIN CONTACT:** Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

**INHALATION:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a Poison Center or doctor/physician.

**EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 min. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**INGESTION:** Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

**MOST IMPORTANT SYMPTOMS/EFFECTS (acute & delayed):** Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

**INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:** Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**GENERAL INFORMATION:** Take off all contaminated clothing immediately. If exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## SECTION V - FIREFIGHTING MEASURES

**SUITABLE EXTINGUISHING MEDIA:** Alcohol resistant foam, water fog, dry chemical powder, Carbon dioxide (CO<sub>2</sub>).

**INSUITABLE EXTINGUISHING MEDIA:** Water. Do not use water jet as an extinguisher, as this will spread the fire.

**SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:** Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

**SPECIAL PROTECTIVE EQUIPMENT & PRECAUTIONS FOR FIREFIGHTERS:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**FIRE FIGHTING (Equipment/instructions):** In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

**SPECIFIC METHODS:** Use standard firefighting procedures and consider the hazards of other involved materials.

**GENERAL FIRE HAZARDS:** Flammable liquid and vapor.

## SECTION VI - ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART



**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. **Large spills:** stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. **Small spills:** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**ENVIRONMENTAL PRECAUTIONS:** Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

## SECTION VII - HANDLING AND STORAGE

**PRECAUTIONS FOR SAFE HANDLING:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before re-use. Observe good industrial hygiene practices.

**CONDITIONS FOR SAFE STORAGE** (including any incompatibilities): Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

## SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

### EXPOSURE LIMITS:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Material:	CAS #:	Type:	Value:
Butyl Cellosolve/Glycol	111-76-2	PEL	240 mg/m <sup>3</sup> , 50 ppm
Ethylbenzene	100-41-4	PEL	435 mg/m <sup>3</sup> , 100 ppm
Isopropyl Benzene	98-82-8	PEL	245 mg/m <sup>3</sup> , 50 ppm
Xylene	1330-20-7	PEL	435 mg/m <sup>3</sup> , 100 ppm

### US. ACGIH Threshold Limit Values

Material:	CAS #:	Type:	Value:
2-Butoxyethylacetate	112-07-2	TWA	20 ppm
Butyl Cellosolve/Glycol	111-76-2	TWA	20 ppm
Ethylbenzene	100-41-4	TWA	20 ppm
Isopropyl Benzene	98-82-8	TWA	50 ppm
Trimethyl Benzene	25551-13-7	TWA	25 ppm
Trimethyl Benzene	95-63-6	TWA	25 ppm
Xylene	1330-20-7	STEL	150 ppm
		TWA	100 ppm

## CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

US. NIOSH: Pocket Guide to Chemical Hazards

Material:	CAS #:	Type:	Value:
2-Butoxyethylacetate	112-07-2	TWA	33 mg/m3, 5 ppm
Butyl Cellosolve/Glycol	111-76-2	TWA	24 mg/m3, 5 ppm
Ethylbenzene	100-41-4	STEL	545 mg/m3, 125 ppm
		TWA	435 mg/m3, 100 ppm
Isopropyl Benzene	98-82-8	TWA	245 mg/m3, 50 ppm
Trimethyl Benzene	95-63-6	TWA	125 mg/m3, 25 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Material:	CAS #:	Type:	Value:
Glycol Ether PM Acetate	108-65-6	TWA	50 ppm

4[a^a]US^&gt;L [fHS^gW

359;: 4[a^a]US^7 baegdW V[UW

B M ZgVah/

Butyl Cellosolve/Glycol Ether EB

Ethylbenzene

Xylene

KVj Z

200 mg/g

0.15 g/g

1.5 g/g

9ZiZg^cVci^

Butoxyacetic acid (BAA), with hydrolysis

Sum of mandelic acid &amp; phenylglyoxylic acid

Methylhippuric acids

HeZX^b Zc^H^b eac^1^b Z

Creatinine in urine

Creatinine in urine

Creatinine in urine

\*for sampling details, please see the source

: nedhj gZ^&lt;j ^YZ^acZh

J #H^8Va[dgc^VD: Ah/H^c^YZh^cM^dc

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Glycol Ether PM Acetate (CAS 108-65-6)

Isopropyl Benzene (CAS 98-82-8)

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

J #H^ Minnesota Haz Subs/H^c^YZh^cM^dc applies

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Isopropyl Benzene (CAS 98-82-8)

Skin designation applies.

Skin designation applies.

J #H^ Tennessee OELs/H^c^YZh^cM^dc

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Isopropyl Benzene (CAS 98-82-8)

Can be absorbed through the skin.

Can be absorbed through the skin.

J #H^NIOSH Pocket Guide to Chemical Hazards: Skin designation

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Isopropyl Benzene (CAS 98-82-8)

Can be absorbed through the skin.

Can be absorbed through the skin.

J #H^OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Isopropyl Benzene (CAS 98-82-8)

Can be absorbed through the skin.

Can be absorbed through the skin.

# CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART



APPROPRIATE ENGINEERING: Explosion-proof general and local exhaust ventilation.

RESPIRATORY PROTECTION: Good general ventilation (typically 10 air changes per hour should be used. Ventilation rates should be matched to conditions.

THERMAL HAZARDS: If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

INDIVIDUAL PROTECTION MEASURES (personal protective equipment): **Eye/face protection:** Chemical respiratory with organic vapor cartridge and full facepiece. **Hand protection:** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. **Other:** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Chemical respirator with organic vapor cartridge and full facepiece. Wear appropriate thermal protective clothing, when necessary. **General hygiene measures:** When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.



**CLASSIC HOT ROD BLACK ACTIVATORY SLOW**

#50204 - 1 QUART

**SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE:	Colorless liquid
ODOR:	Solvent
ODOR THRESHOLD:	Not Available
pH@25°C:	Not Applicable
MELTING/FREEZING POINT:	-82.3°F (-63.5°C)
INITIAL BOILING POINT:	336°F (168.89°C)
FLASHPOINT:	112°F (44.4°C)
EVAPORATION RATE:	Not available
FLAMMABILITY (Solid, Gas):	Not Applicable
AUTO-IGNITION TEMPERATURE:	645°F (340.56°C)
DECOMPOSITION TEMPERATURE:	Not Available
BOILING RANGE:	134 - 137°F
EVAPORATION RATE:	Not Available
LOWER FLAMMABLE LIMIT:	Not Available
UPPER FLAMMABLE LIMIT:	Not Available
LOWER EXPLOSIVE LIMIT:	Not Available
UPPER EXPLOSIVE LIMIT:	Not Available
VAPOR PRESSURE:	- # ] EV
VAPOR DENSITY (air=1):	Not Available
RELATIVE DENSITY:Y	Not Available
VISCOSITY:	Not Available
SOLUBILITY (water):	Not Available
PARTITION COEFFICIENT (n-octanol/water)	Not Available
DENSITY:	Not Available
FLAMMABILITY CLASS:	0.88 g/cm <sup>3</sup>
PERCENT VOLATILE:	Combustible II
	62.5 w/w % By Weight
	65.83 v/v % By Volume
SPECIFIC GRAVITY:	0.88
VOC(weight %):	5.03 lb/gal (Actual VOC-With Water With Exempts)
	5.03 lb/gal (Regulatory VOC-Less Water Less Exempts)
	602.31 g/L (Actual VOC-With Water With Exempts)
	602.31 g/L (Regulatory VOC-Less Water Less Exempts)

**SECTION X - STABILITY AND REACTIVITY**

STABILITY: Stable under normal conditions.

REACTIVITY: This product is stable and non-reactive under normal conditions of use, storage and transport.

CONDITIONS TO AVOID: Heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

COMPATIBLE MATERIALS: Strong acids, strong oxidizing agents, Halogens.

HAZAROUS DECOMPOSITION PRODUCTS: No hazardous decomposition products are known.



# CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

## SECTION XI - TOXICOLOGICAL INFORMATION

LIKELY ROUTE OF EXPOSURE: Inhalation, eye contact, skin contact, ingestion.

INHALATION: Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

EYE CONTACT: Cause serious eye irritation.

SKIN CONTACT: Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

INGESTION: Harmful if swallowed

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS: Headache, nausea, vomiting, severe eye irritation. Symptoms may include stinging, tearing, redness, swelling and blurred vision. May cause respiratory irritation.

Difficulty in breathing. Skin irritation. May cause redness, swelling, and blurred vision. May cause an allergic skin reaction.

Dermatitis, rash. Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. May cause an allergic skin reaction.

May cause respiratory irritation.

### TOXICITY:

MATERIAL:	LD50:	LC50:
2-Butoxyethylacetate	Dermal: 1,500 mg/kg (rabbit) Oral: 2,400 mg/kg (rat)	N/A
Butyl Cellosolve/Glycol Ether EB	Dermal: 400 mg/kg (rabbit) Oral: 1.2 g/kg (guinea pig) 1.2 g/kg (mouse) 0.32 g/kg (rabbit) 560 mg/kg (rat)	Inhalation: 700 ppm, 7 hours (mouse) Inhalation: 450 ppm, 4 hours (rat)
Ethylbenzene	Dermal: 17,800 mg/kg (rabbit) Oral: 3,500 mg/kg (rat)	
Isopropyl Benzene	Oral: 1,400 mg/kg (rat)	Inhalation: 2,000 ppm, 7 hours (mouse) Inhalation: 24.7 mg/l, 2 hours (mouse) Inhalation: 8,000 ppm, 4 hours (rat)
Trimethyl Benzene	Oral: 8,970 mg/kg (rat)	
Trimethyl Benzene	Dermal: >3,160 mg/kg (rabbit) Oral: 6 g/kg (rat)	Inhalation: >2,000 ppm, 48 Hrs (rat)
Xylene	Dermal: >43 g/kg (rabbit) Oral: 1,590 mg/kg (mouse) 3,523-8,600 mg/kg (rat)	Inhalation: 3,907 mg/l, 6 hours (mouse) Inhalation: 6,350 mg/l, 4 hours (rat)

\*Estimates for product may be based on addition component data not shown.

**Skin corrosion/irritation:** Causes skin irritation.

**Serious eye damage/ eye irritation:** causes serious eye irritation.

**Respiratory sensitization:** May cause allergy or asthma symptoms or breathing difficulties if inhaled

**Skin sensitization:** May cause an allergic skin reaction.

**Germ cell mutagenicity:** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity:** Suspected of causing cancer.

**IARC Monographs. Overall Evaluation of Carcinogenicity:**

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2) - 3 Not classifiable as to carcinogenicity to humans

Ethylbenzene (CAS 100-41-4) - 2b Possibly carcinogenic to humans.

Isopropyl Benzene (CAS 98-82-8) - 2b Possibly carcinogenic to humans

Xylene (CAS 1330-20-7) - 3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) - Not listed**

**Reproductive toxicity:** Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.

Excel Products US, Inc.,

2921 Syene Rd, Madison, WI 53713

Tel: (800) 957-0848 Fax: (608) 274-5313

Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)

Website: [www.excelproducts.net](http://www.excelproducts.net)





# CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

**Specific target organ toxicity** (single exposure): May cause respiratory irritation.

**Specific target organ toxicity** (repeated exposure): Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard:** Not an aspiration hazard.

**Chronic effects:** Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: Toxic to aquatic life with long lasting effects.

Material:	LC50 (fish)	EC50 (crustacea)
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	Inland silverside (Menidia berylina) 1250mg/l, 96 hours	Water flea (Daphnia magna) 1.37-4.4 mg/l, 48 hours
Ethylbenzene (CAS 100-41-4)	Fathead Minnow (pimephales promelas) 7.5-11 mg/l, 96 hours	Brine Shrimp (Artemia sp.) 3.55-11.29 mg/l, 48 hours
Isopropyl Benzene (CAS 98-82-8)	Rainbow trout, donaldson trout (oncorhynchus mykiss) 2.7 mg/l, 96 hours	n/a
Trimethyl Benzene (CAS 95-63-6)	Fathead Minnow (pimephales promelas) 7.19-8.28 mg/l, 96 hours	n/a
Xylene (CAS 1330-20-7)	Bluegill (Lepomis macrochirus) 7.711-9.591 mg/l, 96 hours	n/a

## SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

**Disposal instructions:** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Disposal of contents/container in accordance with local/regional/national/international regulations. **Local disposal regulations:** Dispose in accordance with all applicable regulations. **Hazardous waste code:** The waste code should be assigned in discussion between the user, the producer and the waste disposal company. **Waste from residues/unused products:** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: disposal instructions). **Contaminated packaging:** since emptied containers may retain product residue, follow label warning even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**CLASSIC HOT ROD BLACK ACTIVATORY SLOW**

#50204 - 1 QUART



**SECTION XIV - TRANSPORT INFORMATION** - The following transportation information is provided based on the manufacture's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

**US GROUND (DOT) SHIPPING INFORMATION:**

UN NUMBER: UN1263

PROPER SHIPPING NAME: PAINT related material including paint thinning, drying, removing, or reducing compound, marine pollutant

TRANSPORT HAZARD CLASS: 3

PACKAGING GROUP: III

SUBSIDIARY RISK: 3

LABELS: 3

PACKING GROUP: II

ENVIRONMENTAL HAZARDS - MARINE POLLUTANT: Yes

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

SPECIAL PROVISIONS: 149, B52, IB2, T4, TP1, TP8, TP28

PACKAGING EXCEPTIONS: 150

PACKAGING NON BULK: 173

PACKAGING BULK: 242

**ATA:**

UN NUMBER: UN1263

UN PROPER SHIPPING NAME: Paint related material (including paint thinning or reducing compounds)

TRANSPORT HAZARD CLASS: 3

PACKING GROUP: II

ENVIRONMENTAL HAZARDS: NO

ERG CODE: 3L

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

PASSENGER &amp; CARGO AIRCRAFT: Allowed

CARGO ONLY AIRCRAFT: Allowed

**IMDG**

UN NUMBER: UN1263

UN PROPER SHIPPING NAME: Paint (including paint, lacquer, enamel, stain, shellac, varnish polish, liquid filler and liquid laquer base) or paint related material (including paint thinning or reducing compound)

TRANSPORT HAZARD CLASS: 3

PACKING GROUP: II

ENVIRONMENTAL HAZARDS - MARINE POLLUTANT: Yes

EmS: F-E, S-E

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

TRANSPORT IN BULK (according to annex II of MARPOL 73/78 and the IBC Code): Not established.

GENERAL INFORMATION: DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

# CRYSTAL CLEAR

#82004 - 1 QUART

**SECTION XV - REGULATORY INFORMATION**

**US FEDERAL REGULATIONS:** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. One or more component are not listed on TSCA

**TSCA section 12(b) Export Notification (40 CFR 707, Subpt. D):** Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4):**

2-Butoxyethylacetate (CAS 112-07-2)-Listed

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)-Listed

Ethylbenzene(CAS 100-41-4)-Listed

Isopropyl Benzene (CAS 98-82-8)-Listed

Xylene (CAS 1330-20-7)-Listed

**SARA 304 Emergency release notification:** Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)-**Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA):**

Hazard Categories: Immediate Hazard-yes

Delayed Hazard-Yes, Fire Hazard-yes, Pressure Hazard-No

Reactivity Hazard-No

**SARA 302 Extremely hazardous substance:** Not listed.

**SARA 311/312 Hazardous chemical:** No

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:	CAS #:	% BY WT.
COMPONENT NAME:		
Xylene	1330-20-7	30-50
Ethylbenzene	100-41-4	5-10
Isopropyl Benzene	98-82-8	0-5
Toluene	108-88-3	0-5
Trimethyl Benzene	95-63-6	0-5

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethylbenzene (CAS 100-41-4)

Isopropyl Benzene (CAS 98-82-8)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated

**Safe Drinking Water Act (SDWA)**

Not regulated

**Drug Enforcement Administration (DEA):**

**List 2, essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical code number:**

Toluene (CAS 108-88-3) - 6594

**List 1 & 2 Exempts Chemical Mixtures (21 CFR 1310.12(c))**

Toluene (CAS 108-88-3) - 35 % WV

**DEA Exempt Chemical Mixtures Code Number:**

Toluene (CAS 108-88-3) - 594

Excel Products US, Inc.,

2921 Syene Rd, Madison, WI 53713

Tel: (800) 957-0848 Fax: (608) 274-5313

Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)

Website: [www.excelproducts.net](http://www.excelproducts.net)

# CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

## US. State Regulations

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not Listed

**US. California Candidate Chemicals List. Safer consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3 sub'd a)**

2-Butoxyethylacetate (CAS 112-07-2)  
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)  
Ethylbenzene (CAS 100-41-4)  
Isopropyl Benzene (CAS 98-82-8)  
Trimethyl Benzene (CAS 25551-13-7)  
Trimethyl Benzene (CAS 95-63-6)  
Xylene (CAS 1330-20-7)

## US. Massachutes RTK-Substance List

2-Butoxyethylacetate (CAS 112-07-2)  
Ethylbenzene (CAS 100-41-4)  
Isopropyl Benzene (CAS 98-82-8)  
Trimethyl Benzene (CAS 25551-13-7)  
Trimethyl Benzene (CAS 95-63-6)  
Xylene (CAS 1330-20-7)

## US. New Jersey Worker and Community Right-to-Know Act.

2-Butoxyethylacetate (CAS 112-07-2)  
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)  
Ethylbenzene (CAS 100-41-4)  
Isopropyl Benzene (CAS 98-82-8)  
Trimethyl Benzene (CAS 25551-13-7)  
Trimethyl Benzene (CAS 95-63-6)  
Xylene (CAS 1330-20-7)

## US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethylacetate (CAS 112-07-2)  
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)  
Ethylbenzene (CAS 100-41-4)  
Isopropyl Benzene (CAS 98-82-8)  
Trimethyl Benzene (CAS 25551-13-7)  
Trimethyl Benzene (CAS 95-63-6)  
Xylene (CAS 1330-20-7)

## US. Rhode Island RTK

2-Butoxyethylacetate (CAS 112-07-2)  
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)  
Ethylbenzene (CAS 100-41-4)  
Isopropyl Benzene (CAS 98-82-8)  
Trimethyl Benzene (CAS 25551-13-7)  
Trimethyl Benzene (CAS 95-63-6)  
Xylene (CAS 1330-20-7)

## US. - California Proposition 65 - CRT: Listed date/Carcinogenic Substance

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004

**CLASSIC HOT ROD BLACK ACTIVATORY SLOW**

#50204 - 1 QUART

## INTERNATIONAL INVENTORIES:

Country(s) or Region:	Inventory name:	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European inventory of Existing commercial Chemical Substances (EINECS)	No
Europe	European List of Notified chemical Substances (ELINCS)	No
Japan	Inventory of Existing and new Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

\*A "yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s). A "no" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

This product contains no chemicals known to the state of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)

**SECTION XVI - OTHER INFORMATION**

HMIS Health:	2
HMIS Flammability:	3
HMIS Reactivity:	0

DISCLAIMER: WARNING! KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN! The information contained in this SDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, or fire prevention as necessary or appropriate to use and understand the data in this SDS.

Excel Products US, Inc.,  
2921 Syene Rd, Madison, WI 53713  
Tel: (800) 957-0848 Fax: (608) 274-5313  
Email: [marketing@excelproducts.net](mailto:marketing@excelproducts.net)  
Website: [www.excelproducts.net](http://www.excelproducts.net)