

CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

SECTION I - MANUFACTURERS INFORMATION

PRODUCT NUMBER: 50204
 PRODUCT NAME: Crystal Clear
 DATE PREPARED: 02.07.2019
 REVISION DATE: 06.14.2019

COMPANY: EXCEL AUTOBODY PRODUCTS
 ADDRESS: 2921 SYENE ROAD
 CITY: MADISON, WI 53713
 PHONE: (800) 957-0848
 EMERGENCY PHONE: (800) 424-9300

SECTION II - HAZARDOUS INGREDIENTS

CLASSIFICATION:

Flammable Liquids	Category 3
Acute toxicity, oral	Category 4
Acute toxicity, dermal	Category 4
Acute toxicity, inhalation	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Sensitization, respiratory	Category 1
Sensitization, skin	Category 1
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
Specific target organ toxicity, repeated exposure	Category 1
Hazardous to the aquatic environment, (acute hazard)	Category 2
Hazardous to the aquatic environment, (long - term hazard)	Category 2
OSHA defined hazards	Not Classified

SIGNAL WORD: **DANGER!**

PICTOGRAMS:

**HAZARD STATEMENTS:**

H226 Flammable liquid and vapor
 H315 Causes skin irritation
 H320 Causes eye irritation
 H332 Harmful if inhaled
 H335 May cause respiratory irritation
 H341 Suspected of causing genetic defects
 H350 May cause cancer
 H361 Suspected of damaging fertility or the unborn child
 H373 Causes damage to organs through prolonged or repeated exposure

Excel Products US, Inc.,
 2921 Syene Rd, Madison, WI 53713
 Tel: (800) 957-0848 Fax: (608) 274-5313
 Email: marketing@excelproducts.net
 Website: www.excelproducts.net



CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

PRECAUTIONARY STATEMENTS:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surface - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P302+352	IF ON SKIN: Wash with soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.
P308+313	IF exposed or concerned: get medical advice/attention.
P312	Call a POISON CENTER or a doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P332+313	If skin irritation occurs: get medical advice/attention.
P337+313	If eye irritation persists get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370+378	In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction.
P403+233	Store in a well ventilated place. Keep container tightly closed.
P403+235	Store in a well ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to an approved waste disposal plant.

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

MATERIAL:	CAS #:	WEIGHT %:
Hexamethylene Diisocyanate	28182-81-2	30-50
Trimethyl Benzene	25551-13-7	5-20
Trimethyl Benzene	95-63-6	5-20
Xylene	1330-20-7	5-20
2-Butoxyethylacetate	112-07-2	5-15
Glycol Ether PM Acetate	108-65-6	5-15
Butyl Cellosolve/Glycol Ether EB	111-76-2	0-5
Ethylbenzene	100-41-2	n/a
Isopropyl Benzene	98-82-8	n/a

CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

SEE SECTIONS VIII, XI, XII FOR TOXICOLOGICAL INFORMATION.

SECTION IV - FIRST AID MEASURES

SKIN CONTACT: Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a Poison Center or doctor/physician.

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 min. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

INGESTION: Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

MOST IMPORTANT SYMPTOMS/EFFECTS (acute & delayed): Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

GENERAL INFORMATION: Take off all contaminated clothing immediately. If exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

SECTION V - FIREFIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Alcohol resistant foam, water fog, dry chemical powder, Carbon dioxide (CO₂).

INSUITABLE EXTINGUISHING MEDIA: Water. Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL: Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

SPECIAL PROTECTIVE EQUIPMENT & PRECAUTIONS FOR FIREFIGHTERS: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

FIRE FIGHTING (Equipment/instructions): In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

SPECIFIC METHODS: Use standard firefighting procedures and consider the hazards of other involved materials.

GENERAL FIRE HAZARDS: Flammable liquid and vapor.

SECTION VI - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them.

Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

CRYSTAL CLEAR

#82004 - 1 QUART



METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. **Large spills:** stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. **Small spills:** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

ENVIRONMENTAL PRECAUTIONS: Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before re-use. Observe good industrial hygiene practices.

CONDITIONS FOR SAFE STORAGE (including any incompatibilities): Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Material:	CAS #:	Type:	Value:
Butyl Cellosolve/Glycol	111-76-2	PEL	240 mg/m ³ , 50 ppm
Ethylbenzene	100-41-4	PEL	435 mg/m ³ , 100 ppm
Isopropyl Benzene	98-82-8	PEL	245 mg/m ³ , 50 ppm
Xylene	1330-20-7	PEL	435 mg/m ³ , 100 ppm

CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

US. ACGIH Threshold Limit Values

Material:	CAS #:	Type:	Value:
2-Butoxyethylacetate	112-07-2	TWA	20 ppm
Butyl Cellosolve/Glycol	111-76-2	TWA	20 ppm
Ethylbenzene	100-41-4	TWA	20 ppm
Isopropyl Benzene	98-82-8	TWA	50 ppm
Trimethyl Benzene	25551-13-7	TWA	25 ppm
Trimethyl Benzene	95-63-6	TWA	25 ppm
Xylene	1330-20-7	STEL	150 ppm
		TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Material:	CAS #:	Type:	Value:
2-Butoxyethylacetate	77-58-7	TWA	0.1 mg/m ³
Butyl Cellosolve/Glycol	100-41-4	STEL	545 mg/m ³
Ethylbenzene		TWA	125 ppm, 435 mg/m ³
Isopropyl Benzene	98-82-8	TWA	100 ppm, 245 mg/m ³
Trimethyl Benzene	79-20-9	STEL	50 ppm, 760 mg/m ³
Trimethyl Benzene		TWA	250ppm
Xylene	108-88-3	STEL	200 ppm, 610 mg/m ³
		TWA	150 ppm, 560 mg/m ³
	95-63-6	TWA	100ppm, 375 mg/m ³
			125mg/m ³
			25 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Material:	CAS #:	Type:	Value:
Glycol Ether PM Acetate	108-65-6	TWA	50 ppm

Excel Products US, Inc.,
 2921 Syene Rd, Madison, WI 53713
 Tel: (800) 957-0848 Fax: (608) 274-5313
 Email: marketing@excelproducts.net
 Website: www.excelproducts.net



CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

4[a^aY[US^>L [fHS^gW

359;: 4[a^aY[US^j baegW V[UW

B ViZgVah/

Ethylbenzene

Toluene

Xylene

KVj Z

0.15 g/g

0.3 mg/g

0.03 mg/l

0.02 mg/l

1.5 g/g

9ZiZp ^Vci °

Sum of mandelic acedc& phenylglyoxylic acid

o-Cresol, with hydrolysis

Toluene

Toluene

Methylhippuric acids

HeZX^b Zc^HMo eat^1 ^b Z

Creatinine in urine

Creatinine in urine

Urine

Blood

Creatinine in urine

*for sampling details, please see the source

: nœdhj g^<j ^YZ^acZh

J #H^"8Vaf[dc^VD: Ah^H ^c^YZh^cVi ^dc

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Glycol Ether PM Acetate (CAS 108-65-6)

Isopropyl Benzene (CAS 98-82-8)

J #H^" Minnesota Haz Subs/H^ ^c^YZh^cVi ^dc applies

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Isopropyl Benzene (CAS 98-82-8)

J #H^" Tennessee OELs/H^ ^c^YZh^cVi ^dc

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Isopropyl Benzene (CAS 98-82-8)

J #H^"NIOSH Pocket Guide to Chemical Hazards: Skin designation

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Isopropyl Benzene (CAS 98-82-8)

Can be absorbed through the skin.

Can be absorbed through the skin.

J #H^"OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Isopropyl Benzene (CAS 98-82-8)

Can be absorbed through the skin.

Can be absorbed through the skin.

CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

US. State Regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not Listed

US. California Candidate Chemicals List. Safer consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3 sub'd

Bis(1,2,2,6 -Pentamethyl-4-piperidiny) Sebacate (CAS 41556-26-7)

Ethylbenzene (CAS 100-41-4)

Isopropyl Benzene (CAS 98-82-8)

Toluene (CAS 108-88-3)

Trimethyl Benzene (CAS 25551-13-7)

Trimethyl Benzene (CAS 95-63-6)

Xylene (CAS 1330-20-7)

US. Massachutes RTK-Substance List

Ethylbenzene (CAS 100-41-4)

Isopropyl Benzene (CAS 98-82-8)

Methyl Acetate (CAS 79-20-9)

Toluene (CAS 108-88-3)

Trimethyl Benzene (CAS 25551-13-7)

Trimethyl Benzene (CAS 95-63-6)

Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act.

Ethylbenzene (CAS 100-41-4)

Isopropyl Benzene (CAS 98-82-8)

Methyl Acetate (CAS 79-20-9)

Parachlotobenzotriflouride (CAS 98-56-6)

Toluene (CAS 108-88-3)

Trimethyl Benzene (CAS 95-63-6)

Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethylbenzene (CAS 100-41-4)

Isopropyl Benzene (CAS 98-82-8)

Methyl Acetate (CAS 79-20-9)

Toluene (CAS 108-88-3)

Trimethyl Benzene (CAS 25551-13-7)

Trimethyl Benzene (CAS 95-63-6)

Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Ethylbenzene (CAS 100-41-4)

Isopropyl Benzene (CAS 98-82-8)

Toluene (CAS 108-88-3)

Trimethyl Benzene (CAS 95-63-6)

Xylene (CAS 1330-20-7)

Excel Products US, Inc.,

2921 Syene Rd, Madison, WI 53713

Tel: (800) 957-0848 Fax: (608) 274-5313

Email: marketing@excelproducts.net

Website: www.excelproducts.net

CLASSIC HOT ROD BLACK ACTIVATORY SLOW

#50204 - 1 QUART

**US. - California Proposition 65 - CRT: Listed date/Carcinogenic Substanc**

Ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

Isopropyl Benzene (CAS 98-82-8)

Listed: April 6, 2010

US. - California Proposition 65 - CRT: Listed date/Developmetnal Toxin

toluene (CAS 108-88-3)

Listed: January 1, 1991

US. - California Proposition 65 - CRT: Listed date/Female Reproductive Toxin

toluene (CAS 108-88-3)

Listed: August 7, 2009

CALIFORNIA PROPOSITION 65:

This product contains no chemicals known to the state of California to cause cancer, birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov

SECTION XVI - OTHER INFORMATION

HMIS Health: 2

HMIS Flammability: 3

HMIS Reactivity: 0

DISCLAIMER: WARNING! KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN! The information contained in this SDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, or fire prevention as necessary or appropriate to use and understand the data in this SDS.

Excel Products US, Inc.,

2921 Syene Rd, Madison, WI 53713

Tel: (800) 957-0848 Fax: (608) 274-5313

Email: marketing@excelproducts.netWebsite: www.excelproducts.net